



Technical Datasheet

Product:	300µl Pipette Tips
Part No:	350-xxxx
Comments:	Universal Fit



Specification

Product:	<ul style="list-style-type: none">• 300µl Pipette Tips
Dimension, Length:	<ul style="list-style-type: none">• 58mm
Colour, Optical Quality:	<ul style="list-style-type: none">• Natural, virgin, PP, translucent
Low Retention:	<ul style="list-style-type: none">• Low adhesion, ultra-hydrophobic surface PP, 350-4150
Sterility:	<ul style="list-style-type: none">• By e-Beam, 350-4050; 350-4150
Graduation:	<ul style="list-style-type: none">• At 20µl, 50µl, 100µl and 200µl
Nominal Capacity:	<ul style="list-style-type: none">• 300µl
Material / Characteristics:	<ul style="list-style-type: none">• Natural Polypropylene (PP), free of heavy metal and softener• Autoclavable at maximum 121°C• Use temperature -20°C up to 90°C
Product Characteristics:	<ul style="list-style-type: none">• Physiological harmless / non-toxic• Biologically inert• RNase, DNase, DNA and Pyrogen-free• PrecisePointe, features thin walls and small orifice
Packing, Bulk:	<ul style="list-style-type: none">• 1000 Tips/Bag, 10 Bags/Case• Case specifications: 26 x 26 x 18cm; 0.01cu.m; 3.63kg
Packing, Reload:	<ul style="list-style-type: none">• 10x 96 Tips/Rack, 10x Racks/Pack, 10x Packs/Case• Case specifications: 39 x 31 x 34cm; 0.04cu.m; 7.71kg
Packing, Racked:	<ul style="list-style-type: none">• 10x 96 Tips/Rack, 10x Racks/Pack. 5x Packs/Case• Case specifications: 39 x 31 x 34cm; 0.04cu.m; 6.80kg
Storage:	<ul style="list-style-type: none">• In dry condition• Double boxes and master shipper cases originally closed• Storage temperature +4°C to maximal 25 °C• Pallets should not be stacked
Conformities / Regulations:	<ul style="list-style-type: none">• Rack conforms to the SBS footprint/configuration compatible with robotic workstations, multichannel pipettors, and auto-sampling instruments• Compatibility - fits Gilson Pipetman and Eppendorf Research / Reference. For full compatibility see BioPointe table.